



# NANOFLOW

Fiber blowing machine for FTTH fibers (EPFU) up to 3 mm

## Unique fiber protection

If the maximum recommended load on the fiber exceeds the preset torque, the machine stops the blowing process immediately without damaging the fiber. The operator can also use this as an indicator that the fiber has reached the customer, thus suitable for a one-man job.

## Battery-powered (independent of 110V/230V)

## Quick load of fiber and duct.

Easy load and removal of pre-connected products from the machine without cutting.

## Easy-to-read LED display

Showing speed, distance, fiber protection and low battery information.

## Small but powerful

Anodised aluminium construction.  
Easy adjustment of speed and torque

## INCLUDED

2 x 24V 2.0 Ah powerful Lithium-ion battery with quick charger

2 sets of adaptor plates for 1.1-1.2 mm and 1.4-1.6 mm EPFU fiber

Duct adaptors for duct sizes 3, 5, 7, 8 & 10 mm

## POSSIBLE ACCESSORY ADD-ONS

Tripod with quick adaptor  
Item No.: 103-161127005

Shoulder strap  
Item No.: 103-160601074

Reel holder arm for pre-connected fiber  
Item No.: 103-171020001

Steel drive wheel for up to 3 mm fiber  
Item No.: 103-170515001

24V 4.0 Ah Lithium-ion battery  
Item No.: 103-160601043

A wide selection of adaptor plates for any fiber/duct sizes on request

## SPECIFICATIONS



Item No.:	101-160601800
Cable diameter:	0.8-3.0 mm
Duct diameter:	3-10 mm
Blowing distance <sup>1)</sup> :	Up to 1,200 m
Blowing speed <sup>1)</sup> :	Up to 150 m/min
Recommended pressure and airflow <sup>2)</sup> :	Max. 10 bar (200 l/pr. min.)
Weight:	2.8 kg
Length:	212 mm
Width:	104 mm
Height:	139 mm

<sup>1)</sup> Depending on type of microduct and cable.

<sup>2)</sup> Cooled and dried air.

# NANOFLOW VS. NANOFLOW MAX

## Cable and duct diameter guide

FIBER DIAMETER (mm)	NanoFlow MAX										DUCT DIAMETER (mm)
	3	4	5	7	8	8.5	10	12	12.7		
4.5	For fiber size: 0.8-4.5 mm										
4.0	For duct sizes: 3, 4, 5, 7, 8, 8.5, 10, 12 & 12.7 mm										
3.8											
3.5											
3.0											
2.8											
2.6	For fiber size: 0.8-3 mm For duct sizes: 3, 4, 5, 7, 8, 8.5 & 10 mm										
2.4											
2.3											
2.2											
2.1											
2.0											
1.9											
1.8											
1.7											
1.6											
1.5											
1.4											
1.3											
1.2											
1.1											
1.0											
0.9											
0.8											

## Adaptor plates and wheel guide

For fiber size 0.8-3.0 mm  
NanoFlow adaptor plates and drive wheel applies



For micro cable size 3.0-4.5 mm  
NanoFlow MAX adaptor plates and MAX steel wheel applies.



### WARNING:

Do not combine NanoFlow MAX adaptor plates/MAX steel drive wheel with NanoFlow adaptor plates/drive wheel. Only use MAX adaptor plates with MAX steel drive wheel. Look for the written text 'MAX' if in doubt. If you mix the adaptor plates, it can make the machine malfunction.