



PRODUCT OVERVIEW

Fiber Optic Cable Installation Machines



ACCU



ACCU



110/230 V



110/230 V

Model	NanoFlow	NanoFlow MAX	MicroFlow Touch	MicroFlow LOG
Typical Usage	Inside	Inside	Inside	Inside
Fiber/Cable OD	0.8-3 mm	0.8-4.5 mm	0.8-6.5 mm	0.8-6.5 mm
Duct Size OD	3-10 mm	3-12.7 mm	4-16 mm	4-16 mm
Part no. #	101-160601800	101-190911001	101-10051	101-171001001
Max Speed	150 m/min (490 ft)	125 m/min (410 ft)	90 m/min (295 ft)	90 m/min (295 ft)
Pushing Force	-	0-2 kg	-	-
Blowing distance	Up to 1,200 m	Up to 1,200 m	Up to 2,500 m	Up to 2,500 m
Rec. Airflow	200 l/min (7.1 cfm)	200-400 l/min (7.1- 14.1 cfm)	200-500 l/min (7.1-17.7 cfm)	200-500 l/min (7.1-17.7 cfm)
Rec. Pressure	Max. 10 bar air (150 psi)	Max. 10 bar air (150 psi)	8-16 bar air (120-230 psi)	8-16 bar air (120-230 psi)
Length Width Height Weight	212 mm 104 mm 139 mm 2.8 kg (w/o battery)	212 mm 104 mm 139 mm 2.8 kg (w/o battery)	Machine: 250 mm Control Box: 200 mm 150 mm 150 mm 220 mm 80 mm 10.5 kg 1.2 kg	Machine: 250 mm Control Box: 240 mm 150 mm 250 mm 220 mm 80 mm 10.5 kg 2.9 kg
Service requirement	Annually	Annually	Annually or every 350000 m	Annually or every 350000 m
Unique features	<ul style="list-style-type: none"> Fully automatic Unique double fiber protection Battery-powered No tools needed 	<ul style="list-style-type: none"> Unique double fiber protection Adjustable clamping force Tool free installation Lightweight but powerful 	<ul style="list-style-type: none"> Anti-Buckle fiber detection Adjustable torque Preset automatic stop Adjustable speed control 	<ul style="list-style-type: none"> Access to OptiCloud Possibility of job documentation & planned maintenance Anti-buckle fiber detection



PRODUCT OVERVIEW

Fiber Optic Cable Installation Machines



HYDRAULIC



HYDRAULIC



RELINING

HYDRAULIC

Model	MiniFlow RAPID	PowerFlow RAPID	MultiFlow RAPID
Typical Usage	Outside	Outside	Outside
Fiber/Cable OD	3-12 mm	5.5-25 mm	5.5-32 mm
Duct Size OD	7-20 mm	10-63 mm *	10-63 mm *
Part no. #	101-10031	101-40001	101-40002
Max Speed	100 m/min (325 ft)	80 m/min (260 ft)	80 m/min (260 ft)
Pushing Force	0-40 kg	0-125 kg	0-200 kg
Blowing distance	Up to 3,500 m	Up to 5,000 m	Up to 5,000 m
Floating distance	-	Up to 10,000 m	Up to 10,000 m
Rec. Airflow	1,000 l/min (35.3 cfm)	8,000-12,000 l/min (282.5-423.8 cfm)	8,000-12,000 l/min (282.5-423.8 cfm)
Max. air/water Pressure	8-16 bar air (120-230 psi)	16 bar (230 psi)	16 bar (230 psi)
Max. hydraulic pressure	-	110 bar (1595 psi)	110 bar (1595 psi)
Length Width Height Weight	650 mm 225 mm 210 mm 24 kg	950 mm 400 mm 500 mm 45 kg	1050 mm 400 mm 500 mm 51 kg
Service requirement	Annually	Annually	Annually
Unique features	<ul style="list-style-type: none"> • Possible to reverse cable • Flexible adaptability • Adjustable torque, distance and speed measurement 	<ul style="list-style-type: none"> • Rugged, solid construction • Flexible • Tool free installation 	<ul style="list-style-type: none"> • Relining and single cable • Easy adjustable Flex block and inlet • Adjustable Torque Distance and Speed measurement



* Standard duct size OD for PowerFlow RAPID and MultiFlow RAPID: 14-60 mm
 Custom made duct size OD for PowerFlow RAPID and MultiFlow RAPID: 10-13 mm & 61-63 mm

