



# FLOWLUB 2000

Special lubricant for fiber cable and microduct installation.

## Great improvement of blowing length

It is a waterbased product with high lubricating effect. It greatly reduces friction and static electricity. Reduces resistance to a minimum.

## Easy to apply

The lubrication spreads evenly on the cable surface/ inner wall of the duct. It leaves a very thin film of lubricant and does not make a glue effect.

## Low cost

The lubrication is very concentrated, meaning it is very economical to use.

## RECOMMENDED QUANTITY PER 1,000 M (3281 FT):

Duct diameter OD	Quantity of FlowLUB 2000
20-30 mm	60 ml (2 Oz)
30-40 mm	70 ml (2.3 Oz)
40-50 mm	100 ml (3.3 Oz)

*Sharp turns, loops or long blowing lengths will increase the recommended quantity required.*

## PRODUCT USE

Cable and duct prelubrication.

Shake the bottle before use and apply the lubricant in the duct. Place a suitable sponge in the duct and prelubricate the duct with high pressure air.

## SPECIFICATIONS

Item No.:	101-30541
Aspect:	White liquid tiny viscosity
Odour:	None
Viscosity:	120 sec. 4 mm Ford cup at 20°C (68°F)
Gravity:	1.030 +/- 0.03 gr/cm <sup>3</sup>
PH value:	7.5 +/- 0.5
Inflammability:	Non flammable
Temperature:	From - 5°C to + 70°C (23-158°F)
Biodegradability:	Biodegradable
Toxic:	Non-toxic





# FLOWLUB 5000

Special lubricant for fiber cable and micro cable installation.

## Great improvement of blowing length

It is a waterbased product with high lubricating effect. It greatly reduces friction and static electricity.

## Easy to apply

The lubrication spreads evenly on the cable surface/ inner wall of the duct. It leaves a very thin film of lubricant and does not make a glue effect.

## Low cost

The lubrication is very concentrated, meaning it is very economical to use.

## Winter Grade

Available in a special winter version that can handle temperatures down to -10°C/ 14°F.

## PRODUCT USE

Cable and duct prelubrication.

Shake the bottle before use and apply the lubricant in the duct. Place a suitable sponge in the duct and prelubricate the duct with high pressure air.

## RECOMMENDED QUANTITY PER 1,000 M (3281 FT):

Duct diameter OD	Quantity of FlowLUB 5000
4 mm.....	5 ml ( 0.16 Oz) = 30 cm (12") full duct
8 mm.....	10 ml (0.33 Oz)= 20 cm (8") full duct
12 mm .....	15 ml (0.5 Oz) = 15 cm (6") full duct

*Sharp turns, loops or long blowing lengths will increase the recommended quantity required.*

## SPECIFICATIONS

Item No.: .....101-30531  
 Aspect: .....White liquid tiny viscosity  
 Odour: .....Characteristic  
 Viscosity: ..... 30 sec. 4 mm Ford cup at 20°C (68°F)  
 Gravity: ..... 1.030 +/- 0.03 gr/cm<sup>3</sup>  
 PH value: ..... 7.5 +/- 0.5  
 Inflammability: .....Non flammable  
 Temperature: ..... From 0°C to + 70°C (32-158°F)  
 Biodegradability: ..... Biodegradable  
 Toxic: ..... Non-toxic

