



# PRODUCT OVERVIEW



ACCU

| Model                               | PicoFlow RAPID   | MicroFlow Touch   |
|-------------------------------------|--|---|
| Typical Usage                       | Inside   | Inside  |
| Fiber/Cable OD                      | 0.8-3 mm   | 0.8-4.5 mm  |
| Duct Size OD                        | 3-12.7 mm  | 3-12.7 mm   |
| Item No. #                          | 101-231211100  | 101-190911001   |
| Max Speed                           | 90 m/min (295 ft/min) <sup>1</sup>   | 125 m/min (410 ft/min)  |
| Pushing Force                       | 0-2 kg (0-4.4 lbs)   | 0-2 kg (0-4.4 lbs)  |
| Blowing distance                    | Up to 500 m (1640 ft)  | Up to 1,200 m   |
| Rec. Airflow                        | Min. 200 l/min. (7.1 cfm)  | 200-400 l/min (7.1- 14.1 cfm)   |
| Max. Pressure                       | Max. 16 bar (232 psi)  | 10 bar (150 psi)  |
| Length<br>Width<br>Height<br>Weight | 111 mm<br>77 mm<br>87 mm<br>0.590 kg   | 212 mm<br>104 mm<br>139 mm<br>2.8 kg (w/o battery)  |
| Service requirement                 | Annually   | Annually  |
| Unique features                     | <ul style="list-style-type: none"> <li>• Compact handheld machine</li> <li>• Ready to run, seamless field operation</li> <li>• Tool free installation</li> <li>• One more job a day</li> </ul> | <ul style="list-style-type: none"> <li>• Unique double fiber protection</li> <li>• Adjustable clamping force</li> <li>• Tool free installation</li> <li>• Lightweight but powerful</li> </ul> |

<sup>1</sup> Depending on the drill machine used to drive the blowing machine



# PRODUCT OVERVIEW



110/230 V



110/230 V



230 V

| Model   | MicroFlow Touch   | MicroFlow LOG  | EasyFlow SMART  |
|---|---|--|---|
| <b>Typical Usage</b>                          | Inside  | Inside   | Inside/Outside <sup>1</sup>   |
| <b>Fiber/Cable OD</b>                         | 0.8-6.5 mm  | 0.8-6.5 mm   | 4-16 mm   |
| <b>Duct Size OD</b>                           | 4-16 mm   | 4-16 mm  | 8-40 mm   |
| <b>Item No. #</b>                             | 101-10051   | 101-171001001  | 101-211129001   |
| <b>Max Speed</b>                              | 90 m/min (295 ft/min)   | 90 m/min (295 ft/min)  | 80 m/min (260 ft/min)   |
| <b>Pushing Force</b>                          | 0-12 kg   | 0-10 kg  | 0-30.6 kg   |
| <b>Blowing distance</b>                       | Up to 2,500 m   | Up to 2,500 m  | Up to 3,500 m   |
| <b>Rec. Airflow</b>                           | 200-500 l/min (7.1-17.7 cfm)  | 200-500 l/min (7.1-17.7 cfm)   | 1,000-12,000 l/min (35.3-423.8 cfm)   |
| <b>Max. Pressure</b>                          | 16 bar (230 psi)  | 16 bar (230 psi)   | 16 bar (230 psi)  |
| <b>Length<br/>Width<br/>Height<br/>Weight</b> | Machine: 250 mm<br>Control Box: 200 mm<br>150 mm 150 mm<br>220 mm 80 mm<br>10.5 kg 1.2 kg   | Machine: 250 mm<br>Control Box: 240 mm<br>150 mm 250 mm<br>220 mm 80 mm<br>10.5 kg 2.9 kg  | 400 mm<br>620.5 mm<br>340 mm<br>44 kg   |
| <b>Service requirement</b>                    | Annually or every 350000 m  | Annually or every 350000 m   | Annually  |
| <b>Unique features</b>                        | <ul style="list-style-type: none"> <li>• Anti-Buckle fiber detection</li> <li>• Adjustable torque</li> <li>• Preset automatic stop</li> <li>• Adjustable speed control</li> </ul> | <ul style="list-style-type: none"> <li>• Access to OptiCloud</li> <li>• Possibility of job documentation &amp; planned maintenance</li> <li>• Anti-buckle fiber detection</li> </ul> | <ul style="list-style-type: none"> <li>• Fully automatic fiber blowing machine</li> <li>• Equipped with a cable protection system</li> <li>• Fully automatic air supply</li> <li>• Tool free configuration</li> </ul> |

<sup>1</sup> Not to be used in wet environments



# PRODUCT OVERVIEW



HYDRAULIC



HYDRAULIC



HYDRAULIC



HYDRAULIC

RELINING

| Model                   | MiniFlow RAPID  | PowerFlow RAPID  | MultiFlow RAPID   | DuctRod RAPID  |
|-------------------------|---|--|---|--|
| Typical Usage           | Outside   | Outside  | Outside   | Outside  |
| Fiber/Cable OD          | 3-12 mm   | 5.5-25 mm  | 5.5-32 mm   | 9-25 mm  |
| Duct Size OD            | 7-20 mm   | 10-63 mm <sup>1</sup>  | 10-63 mm <sup>1</sup>   | 10-40 mm   |
| Item No. #              | 101-10031   | 101-40001  | 101-40002   | 101-220106001  |
| Max Speed               | 100 m/min (325 ft/min)  | 80 m/min (260 ft/min)  | 80 m/min (260 ft/min)   | 80 m/min (260 ft/min)  |
| Pushing Force           | 0-40 kg   | 0-125 kg   | 0-200 kg  | 0-200 kg   |
| Blowing distance        | Up to 3,500 m   | Up to 5,000 m  | Up to 5,000 m   | -  |
| Pushing distance        | -   | -  | -   | Up to 500 m  |
| Floating distance       | -   | Up to 10,000 m   | Up to 10,000 m  | -  |
| Rec. Airflow            | 1,000 l/min (35.3 cfm)  | 8,000-12,000 l/min (282.5-423.8 cfm)   | 8,000-12,000 l/min (282.5-423.8 cfm)  | -  |
| Max. air/water Pressure | 8-16 bar air (120-230 psi)  | 16 bar (230 psi)   | 16 bar (230 psi)  | -  |
| Max. hydraulic pressure | -   | 110 bar (1595 psi)   | 110 bar (1595 psi)  | 110 bar (1595 psi)   |
| Length                  | 650 mm  | 950 mm   | 1050 mm   | 1050 mm  |
| Width                   | 225 mm  | 400 mm   | 400 mm  | 475 mm   |
| Height                  | 210 mm  | 500 mm   | 500 mm  | 790 mm   |
| Weight                  | 24 kg   | 45 kg  | 51 kg   | 68 kg  |
| Service requirement     | Annually  | Annually   | Annually  | Annually   |
| Unique features         | <ul style="list-style-type: none"> <li>• Possible to reverse cable</li> <li>• Flexible adaptability</li> <li>• Adjustable torque, distance and speed measurement</li> </ul> | <ul style="list-style-type: none"> <li>• Rugged, solid construction</li> <li>• Flexible</li> <li>• Tool free installation</li> </ul> | <ul style="list-style-type: none"> <li>• Relining and single cable</li> <li>• Easy adjustable Flex block and inlet</li> <li>• Adjustable Torque Distance and Speed measurement</li> </ul> | <ul style="list-style-type: none"> <li>• Tool free installation</li> <li>• Adaptable to various manholes</li> <li>• Efficient rod pushing</li> <li>• Adjustable Torque Distance and Speed measurement</li> </ul> |

<sup>1</sup> Standard duct size OD for PowerFlow RAPID and MultiFlow RAPID: 14-60 mm

Custom made duct size OD for PowerFlow RAPID and MultiFlow RAPID: 10-13 mm & 61-63 mm

